

Premium Packing Tape

KRAFT PAPER
FLATBACK TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

A moisture resistant kraft flatback paper tape. Aggressive pressure-sensitive, natural/synthetic rubber adhesive is designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. Designed for use in applications where reduced weight can provide packaging material savings. Approved as packaging tape by U.S. Postal Service and U.P.S. (United Parcel Service). Product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing.

GOVERNMENT COMPLIANCE

PPP-T-42C, Type II
C.I.D. A-A-883, Type II
C.I.D. A-A-1683B

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Kraft Flatback
Adhesive	Natural / Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	60 (16.4 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	45 (197 N/25mm)
Elongation (% at break)	7
Total Thickness (mils) PSTC-133	7.2 (0.18mm)
Color	Brown



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/13

