

ProMask GP

UTILITY PAPER MASKING TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

An economical beige, smooth crepe paper masking tape with a pressure-sensitive synthetic rubber adhesive.

PRODUCT APPLICATION

Can be used for a variety of non-critical tape applications such as hanging paper, poly and poster board.

GOVERNMENT CONFORMANCE

ASTM D6123 Type I
C.I.D. A-A-883B Type I

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Smooth Crepe Paper
Adhesive	Synthetic Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-101	36 (9.8 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	19 (83.2 N/25mm)
Elongation (% at break) PSTC-131	6.4
Total Thickness (mils) PSTC-133	5 (0.127mm)
Quick Stick (oz/in of width) PSTC-5 To Steel	12 (3.3 N/25mm)
Operating Temperature Range	+50°F ~ +180°F (+10°C ~ +93°C)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 8/11

