

i build with **ipg**



HVAC ASSORTMENT

MANUFACTURED IN THE USA BY IPG FOR THE HVAC MARKET



ALF150L GENERAL PURPOSE ALUMINUM FOIL TAPE WITH LINER

Item Number	UPC	Resource Number	Size	Tensile (lb/in)	Adhesion (oz/in)	Thickness (mils)	Elongation (%)	Color	Case
9202-B	0-77922-76193-7	99605	2.0 in x 50 yds	18	175	3.3 w/o liner	3.0	Silver	12

ALF150L is a dead soft aluminum foil tape for seaming and sealing fiberglass duct board, and duct wrap. High tack rubber based adhesive. Recommended minimum application temperature 40°F (4°C). The shiny aluminum backing offers excellent reflective properties (i.e. heat, light). Tested in accordance with UL-723 (ASTM E-84).



ALF175L COLD WEATHER ALUMINUM FOIL TAPE WITH LINER

Item Number	UPC	Resource Number	Size	Tensile (lb/in)	Adhesion (oz/in)	Thickness (mils)	Elongation (%)	Color	Case
9502-B	0-77922-00123-1	99606	2.0 in x 50 yds	18	60	3.5 w/o liner	4.0	Silver	12

ALF175L is a cold weather acrylic tape for seaming and sealing fiberglass duct board and duct wrap. It features vapor barrier integrity, flame retardant, high shear adhesion, UV resistance, and superior bonding in subzero or elevated temperatures. For use in Industrial and HVAC applications. Tested in accordance with UL-723 (ASTM E-84).



ALF201L UL181A-P, UL181B-FX LISTED ALUMINUM FOIL TAPE WITH LINER

Item Number	UPC	Resource Number	Size	Tensile (lb/in)	Adhesion (oz/in)	Thickness (mils)	Elongation (%)	Color	Case
5010-B	0-87143-00222-1	99607	2.5 in x 60 yds	25	60	4.7 w/o liner	1.0	Silver	12

ALF201L is a cold weather acrylic tape for seaming and sealing fiberglass duct board and duct wrap. It features vapor barrier integrity, flame retardant, high shear adhesion, UV resistance, and superior bonding in subzero or elevated temperatures. Designed to be used on duct board and flexible duct systems where UL181A-P and UL181B-FX standards are required.



FSK (FOIL-SCRIM-KRAFT) DUCT SEALING TAPE

Item Number	UPC	Resource Number	Size	Tensile (lb/in)	Adhesion (oz/in)	Thickness (mils)	Elongation (%)	Color	Case
FSK3-B	0-77922-00139-2	99608	3.0 in x 50 yds	43	>100	7.2 w/o liner	2.0	Silver	12

FSK tape is engineered to seam/seal FSK duct board and insulation to enhance appearance and maintain vapor barrier integrity. The aggressive acrylic pressure-sensitive adhesive provides long-lasting adhesion to clean/dry surfaces. Full bond within 24 hours. Remains flexible to resist cracking and lifting. Resistant to mold and mildew. Release coated kraft liner. Tested in accordance with UL-723 (ASTM E-84).



AC698 UL181B-FX LISTED FILM TAPE

Item Number	UPC	Resource Number	Size	Tensile (lb/in)	Adhesion (oz/in)	Thickness (mils)	Elongation (%)	Color	Case
4140-B	0-77922-84140-0	99604	1.88 in x 120 yds	21	42	2.7	130	Blk/White Print	12
4141-B	0-77922-84141-7	99603	1.88 in x 120 yds	21	42	2.7	130	Metallic/Burg-Print	12

Acrylic-based BOPP designed for seaming, closing and repairing flexible ducts. Superior flexibility allows conformability to a variety of shapes. Excellent adhesion in a wide range of temperatures, up to 210°F. UL markings printed on the tape for easy identification. Hand tears, no dispenser needed. UL181B-FX listed. UV resistant. Mold resistant. Two times the footage on a roll than cloth duct tape.



AC50-UL UL181B-FX LISTED DUCT TAPE

Item Number	UPC	Resource Number	Size	Tensile (lb/in)	Adhesion (oz/in)	Thickness (mils)	Elongation (%)	Color	Case
AC50ULS-B	0-77922-99521-9	99609	1.88 in x 60 yds	38	75	14	21	Silver	8

Easy tear straight across or down without curling. Excellent bond to flex duct, sheet metal and other surfaces. Operates in temperatures up to 200°F. Resistant to flame spread, smoke generation, mold growth and humidity. A superior closure system for flexible air ducts and connectors. UL181B-FX listed for use with Class 1 ducts.



AC50 SPRAY ADHESIVE

Item Number	UPC	Resource Number	Net Weight	Spray Pattern	Case
AC 50	0-77922-82758-9	82758	12 Fluid Oz	Web	12

Designed to assist in bonding to several surfaces, including wood, cloth, concrete and sheet metal. Excellent as a primer in HVAC and insulation installation. Contains no methyl chloride; no CFCs. 41 PSI shear strength. Fast tack; pressure sensitive.

HVAC Assortment Planogram



i build with



800-IPG-8273 / 800-474-8273
www.itape.com | E-mail: info@itape.com

©2015 Intertape Polymer Group® • HVAC ASSORTMENT SS • 1748-041515

