

i tape with



RG89

PREMIUM GRADE FILAMENT TAPE



WE ARE PLEASED TO INTRODUCE *RG89 premium strength (680lbs/in) filament tape. RG89 was developed to provide the strength and adhesive characteristics required for heavy-duty applications. RG89 is one of the highest tensile strength products in IPG's filament tape portfolio. In addition to providing a solution for heavy-duty general manufacturing applications, RG89 was designed to help optimize operations and reduce risks in the Oil & Gas industry by helping to prevent the deformation known as "birdcaging" during manufacture and use of Subsea Umbilical cables, Risers and Flow lines (SURF). Similarly, in the Appliance industry, RG89 can be used for securing heavyweight baseloid lift-flap cartons during appliance manufacture and transport.*



ASSOCIATED MARKETS



FEATURES & BENEFITS

- Provides premium strength and holding power in the most demanding applications
- Excellent for bundling and tabbing applications

Backing	Color	Adhesive	Reinforcement	Tensile Strength (lbs/in of width) PSTC-131	90° Adhesion to Steel (oz/in of width) PSTC-101	Elongation (% at break) PSTC-131	Total Thickness (mils) PSTC-133
92 Gauge (23 micron) Polyester	Clear	Synthetic Rubber	Fiberglass	680 (2977 N/25mm)	85 (23.2 N/25mm)	4.5	8 (0.20mm)

i tape with

888-898-7834
www.itape.com | info@itape.com

©2016 Intertape Polymer Group® • RG89 SS • 2830-040416

