




































AMERICAN[®] PERFORMANCE SERIES

Featuring Tapes You Can Rely On

		FEATURE	MAX TEMP. FOR CLEAN REMOVAL	STRENGTH	CONFORMABILITY	MARKET
XT PREMIUM PERFORMANCE		Improved Solvent Resistance	 325°F	 Best	 Extreme	
PG21 PREMIUM GRADE		Improved Temperature Range	 325°F	 Best		
OM PREMIUM GRADE		High Temperature Range & Smooth Backing	 250°F	 Best		
AM MEDIUM GRADE		Improved Conformability	 225°F	 Better		
MM INDUSTRIAL GRADE		One-Piece Clean Removal	 300°F	 Better		
SG MEDIUM GRADE		High Tack	 180°F	 Good		
PM PRODUCTION MASKING		Value Tape	 180°F	 Good	 Limited	



PREMIUM SOLVENT RESISTANCE

- Enhanced backing to ensure superior resistance to solvents
- Superior adhesion to a variety of surfaces
- Resists paint-bleed through



HIGH TEMPERATURE

- Fine structured crepe backing sets the standard for sharp paint lines
- Resists paint-bleed through
- Specifically designed adhesive formula to ensure superior adhesion to a variety of surfaces
- High temperature resistances with 3-day UV properties



UV RESISTANT

- Exceptional conformability
- Excellent adhesion to backing to provide a secure bond and to prevent lifting and overspray
- Removes cleanly and provides a clean crisp paint line
- 3-day UV resistance



HIGH CONFORMABILITY

- Excellent conformability to a variety of surfaces
- Enhanced vibrant aqua backing for high visibility of masked surfaces
- Resists paint flaking and wet sanding



ONE-PIECE CLEAN REMOVAL

- Strong backing to ensure one-piece clean removal
- Specially formulated to provide a secure bond and to prevent lifting and overspray
- Easy and consistent unwinds to enhance the application process



HIGH TACK

- Smooth unwinds for easy of application
- Great holding power with clean removal from a variety of surfaces



VALUE

- All-Purpose product for non-critical applications