

i tape



Cactus Intertape brand

ATA 200, 400, 500 & W2080, Y2070

ACRYLIC TRANSFER TAPES

IPG® and Cactus® Adhesive Transfer Tape products all have a solvent based acrylic adhesive on an easy release kraft paper liner. The shear and adhesion properties of the ATA family of products range from good to excellent and are suitable for a broad range of temperatures, and are resistant to UV light. The Adhesive Transfer Tapes are a clean, sleek alternative to screws, nails, glue and other fasteners; and have various applications and adhere well to a variety of surfaces, including: cork, corrugate, decorative plastic trim, fabric, felt, foam, metal, paper and vinyl.

FEATURES & BENEFITS

ALL TAPES

- Easy to die-cut and process
- Consistent release from liner
- Excellent resistance to solvents

ATA 200 & 400

- High tack
- Short term heat resistance up to 250°F

ATA 500

- High shear
- High resistance to plasticizers
- Short term heat resistance up to 400°F

W2080 & Y2070

- Good clarity
- Smooth, flat finish



©2018 Intertape Polymer Group • Acrylic Transfer Tape SS • 06/15/18



800-565-2000 | itape.com





PRODUCT ATTRIBUTES

Style	Adhesive	Liner	Adhesion (oz/in of width)	Thickness w/o Liner (mils)	Total Thickness	Color	Shear
ATA 200	Solvent Acrylic - Glass Filled	Densified Kraft Paper	65 (17.8 N/25mm)	2.0 (0.05mm)	5.7 (0.14mm)	Clear	Good
ATA 400	Solvent Acrylic - Glass Filled	Densified Kraft Paper	87 (23.8 N/25mm)	4.0 (.10mm)	7.7 (0.20mm)	Clear	Good
ATA 500	Solvent Acrylic - Glass Filled	Densified Kraft Paper	90 (24.6 N/25mm)	5.0 (0.127mm)	8.7 (0.22mm)	Clear	Excellent



PRODUCT ATTRIBUTES

Style	Adhesive	Liner	Adhesion to Steel (oz/in of width)	Thickness w/o Liner (mils)	Total Thickness	Color	Shear
W2080	Solvent Acrylic	80# PCK - White	53 (14.7 N/25mm)	2.0 (0.05mm)	8 (0.20mm)	Clear	Excellent
Y2070	Solvent Acrylic	Glassine - Gold	88 (24 N/25mm)	4.0 (.10mm)	10 (0.25mm)	Clear	Good

* UL94-VO Recognized

PRODUCT APPLICATIONS

ATA 200, 400

- Converter applications
- Splicing & tabbing
- Lamination to textured surfaces
- Outdoor displays
- Bonding plastic trim, overlay material, gaskets & foam

ATA 500

- High temperature applications
- High tension applications
- Bonding to LSE substrates

W2080 & Y2070

- Higher temperature applications
- Metal bonding & mounting
- Name plate & touch pad mounting
- Splicing & laminating
- Gasket lamination

MARKETS

- Gasket Fabrication
- Laminators
- Trpphy/Displays
- POP
- Industrial Manufacturing - Paper/Corrugator/ Film Splicing
- Electrical/Electronics



Scan for more info or visit itape.com/doublecoated

