

i tape



INTERPACK™
BRAND PACKAGING SYSTEMS



USC 2020-TB

UNIFORM SEMI-AUTOMATIC CASE SEALER

Interpack's USC grade of case sealers are part of the USA SERIES Uniform Semi-Automatic family. The USC 2020-TB is a top & bottom belt drive case sealer designed and constructed for low to medium volume applications. They are adjustable, operator fed machines that process same sized RSC style cases. Every Interpack™ Case Sealer comes with ET 2Plus tape heads with adaptive technology to provide optimal tape application and wipe down to each of the 3 taped panels of the case.

When you compare features, benefits and value, Interpack™ Case Sealers are the right choice for operators, plant engineers, maintenance and purchasing.



ET 2Plus tape head

MACHINE FEATURES & BENEFITS

- Compact design conserves valuable floor space
- 3mm steel formed and welded construction
- Horizontal self-centering side guides
- 2" top & bottom belt drives with belt over roller technology
- Twin ¼ HP motors will process up to 65 lb cases
- Dual columns for maximum processing stability
- Threaded rod upper head adjustment
- Reversible controls for left or right handed operation
- Tilt up upper tape head for easy roll replacement

THESE MACHINES ARE ENGINEERED TO PROVIDE:

- Economical cost
- Compact footprint to conserve valuable floor space
- Ergonomic, user-friendly operation and case size set up

Scan for more information on Interpack's USA Series, including CAD drawings, manuals and videos!



©2022 Intertape Polymer Group® • USC 2020-TB-ET 2Plus • 042922



800-474-8273 | itape.com

ipg®
intertape
polymer
group®

PRODUCT ATTRIBUTES

CHARACTERISTICS	USC 2020-TB*	USC 2020-TB/3*
Min Case (L x W x H)	6.5" x 6.5" x 5"	6.5" x 6.5" x 5"
Max Case (L x W x H)	Inf x 20" x 21.5"	Inf x 20" x 21.5"
Case Weight	0 - 65 lbs	0 - 65 lbs
Belt Speed	75 ft/min	75 ft/min
Electric	110v., 1ph., 60hz., 6A., (2 x 1/4HP)	110v., 1ph., 60hz., 6A., (2 x 1/4HP)
Tape Width	36 - 48 mm (1.5" - 2")	48 - 72 mm (2" - 3")
Conveyor Height	24" - 30"	24" - 30"
Machine Weight	415 lbs crated	415 lbs crated
Machine Dimensions	43" x 29.5" x 67"	43" x 29.5" x 67"

*Top squeezers close to 8" minimum



Tip-up tape head simplifies roll replacement



Threaded rod upper head lifting



Top & bottom belt drive with belt over roller technology



1/4 HP gear motors to process up to 65 lb cases



2-wheel top squeezer



Horizontal self-centering in-feed guides



Optional 19" long pack tables available with pack horn

OPTIONS & ACCESSORIES

- 3-inch wide tape heads
- Heavy-duty casters (shown above)
- Infeed and exit tables
- Infeed table with "T" rail hold down
- ET Xtreme™ tape heads

DID YOU KNOW?

IPG® is the only North American manufacturer of all 3 types of pressure-sensitive adhesives. Combine Interpack™ machinery and IPG long roll pressure-sensitive tape for greater value. Contact your authorized IPG distributor for details.



Scan for more info or visit itape.com/machines

