

'ARTICLE' DOCUMENT **ALTERNATE TO A SAFETY DATA SHEET (SDS)**

The products listed below are defined as 'articles', which are exempt from OSHA Safety Data Sheet (SDS) requirements. Therefore, SDS have not been constructed for them. These products should not present a health or safety hazard under recommended or normal use. However, misuse of these products may affect product performance or present a potential health and safety hazard. This document was constructed as a courtesy for customers.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Names:	Palisade SA-HT Self Adhered Roofing Underlayment
Company:	Intertape Polymer Group 100 Paramount Drive, Suite 300 Sarasota, Florida 34232
Product Use:	Roof Underlayment
Issue Date:	March 29, 2022
Emergency Phone Number:	1-800-565-2000

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	C.A.S. Number	Weight (%)
Polypropylene	9003-07-0	<30%
Polyethylene Terephthalate (Polyester)	25038-59-9	<5%
Petroleum Asphalt	8052-42-4	>50%
Petroleum Oil	64741-88-4	>15%

3. HAZARDS IDENTIFICATION

Bitumen membrane. Asphalt Odor. Under normal use, this product is not expected to create any health or environmental hazard. Inhalation of dust or asphalt fumes can cause respiratory irritation and/or congestion.





Eye/Skin contact:	Prolonged and/or repetitive contact can cause abrasion and irritation. Contact with molten product will burn unprotected skin and eyes. Should a burn occur, cool burn area immediately with cool, clean, running water until no heat is emitted from the burn area. Cover with light, dry dressing. Do not apply oily ointments or puncture blisters. Obtain medical assistance.
Inhalation:	Avoid breathing dust; it may cause irritation if exposure is prolonged or excessive.
Ingestion:	Products should not be eaten, nor used as food wrapping. May cause irritation to throat, mouth and stomach.

4. FIRST AID MEASURES

If in contact with hot or molten plastic, treat the affected	
area with cool water and seek medical attention.	

5. FIRE FIGHTING MEASURES

Flash point:	Not applicable	
Flammable limits – LEL:	Not applicable	
Flammable limits – UEL:	Not applicable	
Auto ignition temperature:	Not applicable	
Extinguishing media:	Water Spray, Dry Chemical, Foam	
Special firefighting procedures:	Wear full protective equipment and a self-contained	
	breathing apparatus	
Unusual fire and explosion hazards:	Burning is accompanied by melting and dripping which	
	may cause the fire to spread hazardous combustion	
	products carbon monoxide and carbon dioxide.	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective	
equipment, and emergency procedures:	Not applicable
Environmental precautions:	Not applicable
Cleanup methods and materials:	Not applicable



TAPES & FILMS . PACKAGING PRODUCTS & SYSTEMS . BUILDING MATERIALS . ENGINEERED COATED PRODUCTS



7. HANDLING AND STORAGE

Safe handling:	Products may be slippery to walk on when wet. Charges of static electricity may be generated during handling and processing.
Safe storage:	Products are best kept in weather-tight conditions and not exposed to sunlight during storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits:	Not applicable
Engineering controls:	Not applicable
Eye protection:	Not applicable
Skin protection:	Gloves recommended in cases of repetitive contact.
Respiratory protection:	Not required under normal use conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

Auto ignition temperature:	Not applicable
Boiling point:	Not applicable
Color:	Blue
Density:	Not applicable
Evaporation rate:	Not applicable
Flash point:	Not applicable
Melting point:	Not applicable
Physical form:	Solid
pH:	Not applicable
Solubility in water:	Nil
Specific gravity:	Not applicable
Vapor density:	Not applicable
Vapor pressure:	Not applicable
Viscosity:	Not applicable
Volatile percent:	Not applicable

10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	Temperatures above 80°C (175°F)
Materials to avoid:	Consult manufacturer before using as containment as a barrier for chemicals other than water. Very slightly reactive with oxidizing agents, acids, alkalis.
Hazardous polymerization:	Not anticipated under normal use
Hazardous decomposition:	Carbon monoxide, carbon dioxide, oxides of nitrogen and hydrocarbons may be generated during thermal decomposition and combustion.

Page 3 of 4



TAPES & FILMS . PACKAGING PRODUCTS & SYSTEMS . BUILDING MATERIALS . ENGINEERED COATED PRODUCTS



11. TOXICOLOGICAL INFORMATION

Exposure to hazardous chemicals is not anticipated with normal use

12. ECOLOGICAL INFORMATION

Not applicable

13. <u>DISPOSAL INFORMATION</u>

Waste product can be recycled where facilities exist, disposed of in a sanitary landfill or incinerated. Check local regulations before disposal.

14. TRANSPORT INFORMATION

These products are not regulated per U.S. DOT, IATA or IMO.

15. REGULATORY INFORMATION

Chemical inventories:	These products are articles as per TSCA regulations, and therefore exempt from TSCA Inventory listing requirements.	
U.S. Federal regulations:	Contact Intertape Polymer Group	
State regulations:	Contact Intertape Polymer Group	
International regulations:	Contact Intertape Polymer Group	

16. OTHER INFORMATION

National Fire Protection Association (NFPA) Hazard Classification			
Health: 0	Flammability: 1	Reactivity: 0	Special hazards: none

The information in this Article Document is believed to be correct as of the date issued. Intertape Polymer Group (IPG) makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. User is responsible for determining whether the IPG product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an IPG product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the IPG product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Page 4 of 4

