



A REGISTERED TRADEMARK OF INTERTAPE POLYMER INC.

505 Series

TUCK TAPE FLASHING TAPE



DESCRIPTION

This tape is made of a multi-layer UV protected polyethylene film coated with a permanent bond adhesive. The 505 provides maximum protection against water and moisture penetration around windows and doors.

MAIN FEATURES

- Meets all AAMA 711-13 requirements, Type A, Level 2.
- High shear adhesive provides excellent initial tack to surfaces.
- Strong and durable holding power.
- No primer required (AAMA 711-13 Type A) when applied on proper surfaces.
- Film is flexible and conforms well around surfaces.
- Seals around fasteners and nails.
- Water and moisture resistant.
- Prevents air infiltration.
- Excellent resistance to UV.

APPLICATIONS

- Waterproof flashing membrane used to seal openings around windows and doors.
- Recommended on aluminum, wood, wood clad, fiberglass, vinyl windows and doors.
- Recommended on most house wraps, OSB, exterior gypsum and fibre board.
- All above surfaces have to be dry and clean in order to assure proper contact.

TECHNICAL DATA

Colour	Red film with black print
Backing	Multi-layer UV protected polyethylene film
Adhesive	UV cured acrylic
Thickness	9.2 mil (0.23mm)
Adhesion to Steel	100 oz/inch • 109 N/100mm
Adhesion to Backing	100 oz/inch • 109 N/100mm
Adhesion to Polyethylene Vapour Barrier	35 oz/inch • 38 N/100mm
Adhesion to NovaWrap™ Aspire™	80 oz/inch • 87 N/100mm
Adhesion to Tyvek®*	50 oz/inch • 54 N/100mm
Adhesion to OSB	91 oz/inch • 101 N/100mm
Adhesion to Anodized Aluminium	111 oz/inch • 122 N/100mm
Adhesion to Plywood	82 oz/inch • 91 N/100mm
Adhesion to Vinyl	106 oz/inch • 117 N/100mm
Tensile Strength	14 lb/inch • 245 N/100mm
Elongation	650%
VOC (Volatile Organic Compound) content	Estimated 0.0 %
Moisture Vapor Transmission	0.205 perms (g/100in ² .24h)
<i>Test in accordance with ASTM E96</i>	
Water Penetration Rate	0.5 (g/100 in ² .24h)
<i>Test in accordance with ASTM D3816</i>	
Air Permeance Rate	0.0002 (cfm/ft ²)
<i>Test in accordance with ASTM E2178-13</i>	
Application Temperature	-10°C (14°F) • 50°C (122°F)
Service Temperature	-40°C (-40°F) • 65°C (149°F)

STRONG AND DURABLE

EXCELLENT RESISTANCE TO U.V.

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

*Spun bonded polyethylene