ECONOMY Electrical Tape VINYL ECONOMY GRADE ELECTRICAL TAPE

DESCRIPTION

Black vinyl electrical insulating tape consisting of a soft 'plasticized' stabilized PVC film coated with a non-corrosive rubber based adhesive. This tape is resistant to water, oils, acids, alkalis, and other corrosive chemicals. UL listed.

PRODUCT APPLICATIONS

Repair frayed wiring, splicing electrical wiring, protect 'wire-nut' connections, resurface and insulate hand tools, and general purpose maintenance/repair.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/20

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	PVC Film
Adhesive	Rubber / Resin
Tensile Strength (Ibs/in of width) ASTM D1000	14 (61.3 N/25mm)
Adhesion to Steel (oz/in of width) ASTM D1000	16 (4.4 N/25mm)
Elongation (% at break) ASTM D1000	200
Total Thickness (mils) ASTM D1000	7.0 (0.178mm)
Dielectric Strength (volts) ASTM D1000	1000V (max) per mil
Flammability UL510	4 seconds max.
Temperature Resistance	176ºF (80ºC) max.
Color	Black

