

DCP056A

MEDIUM GRADE DOUBLE-COATED PET FILM

DESCRIPTION

Polyester (PET) film coated on both sides with pressure-sensitive acrylic adhesive. Provides excellent adhesion to a variety of surfaces, as well as excellent resistance to oils, some plasticizers, ultraviolet (UV) light, and wide range in temperature.

Aggressive acrylic adhesive system bonds well over a wide range of environmental conditions.

PRODUCT APPLICATION

Core starting, splicing paper and film, mounting and many other general purpose applications that requires the joining of two surfaces. Intended for permanent application.

Product is not repulpable.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 10/20

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	0.5 mil (12.5 μ) PET film
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	80 (21.9 N/25mm)
Tensile Strength (lbs./in) PSTC-131	13 (57 N/25mm)
Elongation (%) PSTC-131	100
Total Thickness w/o liner (mils) PSTC-133	3.5 (0.09mm)
Service Temperature	-40°F to +248°F (-40°C to +120°C)
Liner Type	66# White PCK
Color	Clear

