DCT080A

MEDIUM GRADE DOUBLE-COATED TISSUE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Tissue paper coated on both sides with an aggressive, pressure-sensitive, solvent acrylic adhesive. Provides excellent adhesion to a variety of surfaces as well as excellent resistance to oils, some plasticizers, ultraviolet light (UV) and wide range in temperature.

PRODUCT APPLICATION

Designed for splicing and core starting paper or corrugate. Also for sealing vapor barrier or facing overlap seams on mechanical and other types of insulation. Can be used for bonding and laminating a range of materials such as paper, cloth, vinyl, rigid and flexible plastic.

Product is not repulpable.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Tissue
Solvent Acrylic
60 (16.4 N/25mm) Exposed Side
50 (13.7 N/25mm) Closed (Liner) Side
4.0 (17.5 N/25mm)
4.0
-22°F to +248°F (-30°C to +120°C)
+50°F to +104°F (+10°C to +40°C)
3.3 (0.08 mm)

Liner Type 66# White PCK



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/18

