

DCV960A

SPECIALTY UPVC DOUBLE-COATED TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Flexible, hand tearable vinyl (UPVC) coated both sides with a pressure sensitive solvent-based acrylic adhesive. Engineered to offer excellent adhesion to a variety of surfaces. Features a release treated silicone kraft release liner (white).

PRODUCT APPLICATIONS

Sign positioning, carpet tape (hold-down/positioning), mirror manufacturing, extrusions, mounting and many other applications that requires the permanent joining of two surfaces. Product is not repulpable.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	2.0 mil (50μ) UPVC
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	160 (45 N/25mm)
Adhesion to PE (oz/in of width)	115 (31 N/25mm)
Adhesion to PP (oz/in of width)	166 (45 N/25mm)
Temperature Resistance - short term	+250°F (121°C)
Temperature Resistance - long term	+140°F (60°C)
Total Thickness w/o liner (mils) PSTC-133	8.9 (0.23 mm)
Liner Type / Thickness (mils)	SCK - White 3.2 (0.08 mm)
Color	White



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/12

