G4208

PREMIUM DOUBLE-COATED FOAM TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Cross-linked high density polyethylene, closed cell foam coated on both sides (double-coated) with a permanent bonding acrylic pressure-sensitive adhesive protected by an easy release treated 3 mil PE film liner (Lt. Blue). Flexible foam material is effective for sealing, highly resistant to weathering / oxidation, chemicals, UV light and exposure to varied temperature. Adhesion allows permanent bond to a variety of irregular surfaces.

PRODUCT APPLICATION

For outdoor mounting and joining. For sealing against water, dust and light. Can also be used for general-purpose indoor applications such as mounting and joining nameplates, signs, plaques, point-of-purchase, plastic hooks, mirror trims, etc.

GOVERNMENT CONFORMANCE

'UL' recognized (File No. MH19350)

intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/17

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Closed cell / Cross-linked PE foam
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-3	56.4 (15.4 N/25mm)
Density (PCF)	6
Total Thickness w/o Liner (inch) PSTC-133	1/32" (0.8 mm)

Shear Adhesion (hours) >24 (1" x 1" x 2 kg @ 77°F (25°C)

PSTC-107

Service Temperature (Long term)

-4°F to +212°F (-20°C to +100°C)

Color Black

