### **Y4950**

# DOUBLE-COATED PET FILM TAPE

### INTERTAPE POLYMER GROUP®

## **TECHNICAL DATA SHEET**

#### **DESCRIPTION**

0.5 mil polyester (PET) film coated on both sides with pressure-sensitive acrylic adhesive. Provides exceptional shear strength, good adhesion and very high initial tack allowing immediate/permanent bond to a variety of surfaces (including irregular, porous and LSE surfaces). Offers excellent resistance to plasticizer migration, solvents, chemicals, and U.V. light. Features an easy release 3 mil MOPP film liner (red).

Product is not repulpable.

### PRODUCT APPLICATION

Mounting on ABS and PP plates for industrial grade applications. Self-adhering/joining of rubber and EPDM. Fastening of decorative trims (e.g. PVC profile, stainless steel and plastic parts) and any application that requires the joining of two surfaces.

#### **NOMINAL VALUES**

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

 Backing
 0.5 mil (12.5μ) PET

 Adhesive
 Solvent Acrylic

 Adhesion to Steel (oz/in of width) PSTC-101
 63.5 (1.8 kg/25mm)

 Total Thickness w/o Liner (mils) PSTC-133
 6.3 (0.16mm)

 Shear Adhesion to Steel (hours)
 >24

1" x 1" x 1 kg @ 77°F (25°C) PSTC-107

Service Temperature

(Short Term)

-4°F to +212°F (-20°C to +100°C)

**Color** Clear



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.



