4426

POLYESTER FILM / ROPE FIBER ELECTRICAL TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Puncture resistant polyester film/rope fiber laminated backing and aggressive rubber adhesive make this a low cost all-purpose, electrical insulating tape. Rubber thermosetting adhesive system gives excellent solvent resistance.

PRODUCT APPLICATIONS

Coil and transformer insulation wrap, outerwrap for coils, wire pull-outs for stick wound transformers, lead anchoring and wrapping applications.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing Polyester Film / Rope

Fiber

Backing Thickness 4.0 mil (0.101 mm)

Adhesive Rubber Thermosetting

Color Black, Natural

Total Thickness 6.0 mil (0.165 mm)

Dielectric Strength 5500 Volts **Temp/Class** 130°C / B

Insulation Resistance 10⁴ megohms

Tensile Strength 45 lbs/in (79 N/cm)

Adhesion to Steel 60 oz/in (6.6 N/cm)

Elongation 2%

Storage StabilityVery GoodSolvent ResistanceVery GoodMoisture ResistanceExcellentUL File #E20780CSA File #LR94980

*VDE 0340



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13



