54108 1 MIL CURED RUBBER POLYESTER TAPE

DESCRIPTION

1 mil polyester backing with a tightly cured rubber adhesive. The tape exhibits excellent electrical properties and a high initial cure. The backing provides conformability, abrasion and puncture resistance, and excellent insulating properties.

PRODUCT APPLICATIONS

Coil wrapping, interlayer insulation, tabbing and anchoring. Applications calling for high shear resistance at elevated temperatures.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273 Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Polyester Film
Backing Thickness	1.0 mil (0.025 mm)
Adhesive	Cured Rubber
Color	Off-White
Total Thickness	2.4 mil (0.061 mm)
Dielectric Strength	5000 Volts
Temp/Class	130°C / B
Insulation Resistance	10 ⁶ megohms
Tensile Strength	25 lbs/in (44 N/cm)
Adhesion to Steel	50 oz/in (5.5 N/cm)
Elongation	100%
Electrolytic Corrosion	1.0 Direct/ A, 1*
Flammability	BU 1*
Storage Stability	Excellent
Solvent Resistance	Excellent
Moisture Resistance	Excellent
UL File #	E20780
*VDE 0340	

Creating intertare