6120 POLYESTER HIGH TEMPERATURE MASKING TAPE

DESCRIPTION

Polyester (PET) film backing with a silicone adhesive. Designed to perform in difficult masking operations such as the masking of surfaces during application of durable powder coatings. PET backing provides flexibility/conformability, solvent resistance, and chemical resistance. Removes without leaving residue on surfaces. Precision cut for tear resistance and clean, crisp paint lines.

PRODUCT APPLICATIONS

Used for high temperature masking as in powder coatings and PCB protective masking during various phases of printed circuit board (PCB) production. Also excellent for splicing operations requiring silicone adhesive. Can also be used as autoclave flash tape in metal bonding and composites fabrication.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273 Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/16

INTERTAPE POLYMER GROUP[®] **TECHNICAL DATA SHEET**

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Polyester
Backing Thickness	1.0 mil (0.025 mm)
Adhesive	Silicone
Color	Blue
Total Thickness	3.1 mil (0.079 mm)
Temp. Resistance	to 356°F (180°C)
Tensile Strength	26 lbs/in (114 N/25mm)
Adhesion to Steel	28 oz/in (7.7 N/25mm)
Elongation	120%
Storage Stability	Excellent
Solvent Resistance	Excellent
Moisture Resistance	Excellent

