

# RP24

## 272# PET SPECIALTY FILAMENT TAPE

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### DESCRIPTION

Uni-directional polyester strapping tape with reinforcements and a pressure-sensitive natural rubber adhesive. Excellent adhesion and exceptional shear strength.

### PRODUCT APPLICATION

Packaging of large appliances where carton lift flap must support the weight of one or more appliances. Also for steel and aluminum coil tabbing, packaging and carton closure.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	1.42 mil (0.036 mm) Polyester Film
<b>Adhesive</b>	Natural Rubber / Resin
<b>Adhesion to Steel</b> (oz/in of width) (at 90° peel angle) ASTM D3330	38 (10.4 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) ASTM D3759	272 (1190 N/25mm)
<b>Elongation</b> (% at break) ASTM D3759	27
<b>Total Thickness</b> (mils) ASTM D3652	10.2 (0.26 mm)
<b>Quick Stick</b> (oz/in of width) To Kraft To Steel	3.5 (0.96 N/25mm) 26 (7.1 N/25mm)
<b>Color</b>	Cream



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/13

