## 513

# UTILITY PAPER MASKING TAPE

### INTERTAPE POLYMER GROUP®

## **TECHNICAL DATA SHEET**

#### **DESCRIPTION**

Beige crepe paper masking tape coated with an aggressive pressure-sensitive natural rubber adhesive. Designed primarily as an all-purpose product for non-critical applications.

#### **PRODUCT APPLICATION**

Interior paint masking, textile, carpet seaming, silk screening, mail rooms, golf club shaft (build-up), school bids, and for light-duty bundling, packaging, industrial, manufacturing, splicing and tabbing.

#### **GOVERNMENT COMPLIANCE**

ASTM D6123 / 6123M, Type I C.I.D. A-A-883B, Type I

#### **NOMINAL VALUES**

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Crepe Paper
Adhesive	Natural/Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-101	36 (9.8 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) PSTC-131	19 (83.2 N/25mm)
<b>Elongation</b> (% at break) PSTC-131	10
Total Thickness (mils) PSTC-133	5.0 (0.127mm)
<b>Quick Stick to Steel</b> (oz/in of width) PSTC-5	12 (3.3 N/25mm)
Temperature Resistance	+50°F ~ +180°F (+10°C ~ +82°C)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

EFFECTIVE: 09/17

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

