

XT/PG28A

HIGH TEMP PREMIUM MASKING TAPE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

A high temperature masking tape designed for clean removal from a variety of surfaces after exposure to oven temperatures up to 325°F (163°C) for 30 minutes (times and temperatures are determined by surface). Easy handling, smooth crepe, paper backing with high strength and conformability to irregular surfaces; exceptional cornering. "Solvent Resistant" release coating provides exceptional adhesion to backing at both room temperature and when exposed to elevated temperatures.

PRODUCT APPLICATION

Automotive, truck, bus, and marine masking. Recommended hot to warm removal, but can be removed cold. Performs well with gel-coatings associated with manufacture of boats, spas, etc. Also performs well in wet strip applications. Provides resistance to paint flaking and a clean, well-defined paint line. Not recommended for securing large and/or kraft aprons due to reduced adhesive weight and a flatter adhesive film condition versus PG21. Not recommended for outdoor exposure.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Fine crepe paper
Adhesive	Natural Rubber/Resin
Adhesion to Steel (oz/in of width) PSTC-101	28 (7.7 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	26 (114 N/25mm)
Elongation (% at break) PSTC-131	10
Total Thickness (mils) PSTC-133	7.1 (0.18mm)
Quick Stick to Steel (oz/in of width) To Kraft To Steel	3 (0.8 N/25mm) 14 (3.8 N/25mm)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/20

