157

SINGLE LINER MEDIA BLAST STENCIL – MACHINE CUT

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

High quality, durable stencil coated with a medium tack, rubber-based, pressure sensitive adhesive protected by a clear polyester liner. Features a slot-hole pattern. Rubber is trimmed back ½" along each edge for IBM® cutters.

PRODUCT APPLICATION

Designed and recommended for primed / painted wood, HDU foam-board, and polished surfaces. Design centers must be taped before transferring rubber to substrate. Replaces #117 in 30" IBM® cutter applications.

STANDARD SIZES

30" x 10 yards

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive Medium Tack / Rubber

Total Thickness (mil) 40 (1.02 mm)

PSTC-133

Tensile Strength (lbs/in) 5 (21.9 N/25mm)

PSTC-131

180° Adhesion to Steel (oz/in) 55 (15.06 N/25mm)

PSTC-101

Elongation (% at break) 375

PSTC-131

Punch Track

Liner Color Clear

Recommended Filler #211



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/22



