

223

STENCIL FILLER

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

223 stencil filler is specially formulated to work with the most stencil products' adhesive and create a better bond to the substrate during sandblasting. This extra bond helps small, intricate designs to stay attached to the substrate and not lift when sandblasting pressure is applied. 223 filler is a formulated medium tack adhesive for machine cut products.

COMMON APPLICATIONS

Designed for use with stencil 123, 123Y, 124, 124Y, 154, 154Y, and 129Y. On polished surfaces, it is recommended that a light coat be applied. For best results on frosted, axed, or steeled surfaces, apply two coats.

NOMINAL VALUES

The following data is considered typical and should not be used for technical applications.

Color	Off-White, Milky Tan
Viscosity (@ 72°F)	600 - 1500 cPs
Flash Point	51°F
Solids	13.3% - 14.5%
Solvents	Toluene, Heptane



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/14

