790YS ANCHOR GOLD DOUBLE LINER MEDIA BLAST STENCIL - MACHINE CUT

DESCRIPTION

High quality, durable stencil coated with an advanced, medium tack, rubber-based pressure-sensitive adhesive protected by a clear PET liner. The 15" width will track and process on both IBM® and Gerber® pattern cutters. The 30" width will fit only Gerber® #750 plotter machines. Tractor-feed holes are punched through liner and rubber. The specially treated polyester liner retains cut designs during transfer from plotter to stone.

PRODUCT APPLICATIONS

Single-process and double-process media blast carving of granite or marble. Replaces #790Y in Gerber[®] plotter applications.

STANDARD SIZES

15" x 10 yd 30" x 10 yd 30" x 20 yd

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70° F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



intertape polymer group®

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/22

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	46 (1.17 mm)
Tensile Strength (Ibs/in) PSTC-131	6 (26.28 N/25mm)
180º Adhesion to Steel (oz/in) PSTC-101	45 (12.32 N/25mm)
Elongation (% at break) PSTC-131	400
Punch	Slot
Liner Color	(Inner) Yellow (Outer) Clear
Recommended Filler	#223 #333

ANCHOR

