T136

SINGLE LINER HIGH TACK BLASTLITE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

IPG's answer to vinyl. Specially formulated rubber provides impact resistance and natural flexibility allowing T136 to conform tightly around curves and uneven surfaces. High-tack acrylic adhesive bonds quickly to clean surfaces. Uniform thickness, high quality, conformable, long-lasting, and easy to use. Release-treated paper liner permits easy tear by hand. Un-punched/friction fed. Can also be cut by knife for precise fit. Unlike vinyl, T136 does not contain PVC and can be safely cut using laser method.

PRODUCT APPLICATION

Superior surface protection and seal. Especially for use on raw wood, unprimed HDU, brick or unglazed tile.

STANDARD SIZES

12.5" x 10 yds 18.75" x 10 yds 25" x 10 yds Also available in slit goods

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/22

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive High Tack / Acrylic

Total Thickness (mil) 35 (0.89 mm)

PSTC-133

Tensile Strength (lbs/in) 5.5 (24.09 N/25mm)

PSTC-131

180° Adhesion to Steel (oz/in) 35 (9.58 N/25mm)

PSTC-101

Elongation (% at break) 540

PSTC-131

Punch Unpunched, Hand Cut

Liner Color White



