283 Natural HEAVY DUTY BOX MAKERS' TAPE

INTERTAPE POLYMER GROUP® **TECHNICAL DATA SHEET**

DESCRIPTION

Heavy duty fiberglass reinforced natural kraft box maker's tape manufactured with wateractivated adhesive.

PRODUCT APPLICATION

Used for sealing the "manufacturers joint" on cartons in a box-making factory. Works well on recycled cartons. Recommend using on large and extra large size boxes.

PHYSICAL PROPERTIES:

Caliper **CD** Tensile

10.6 mils (0.27mm) 74 lbs/in (324 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C): Finago:

83

2/0	36
2/1	55
5/0	66
15/0	87

McClaurin:



intertape polymer group™

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 03/16

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Top Piv:

Bottom Ply:

Laminating Adhesive:

Water-Activated Adhesive:

CD Reinforcement

High Melt Index Polypropylene Based Co-Polymer

30 lb (49 g/m²)

57 lb (93 g/m²)

Natural Kraft Paper

Natural Kraft Paper

Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911

(2-2-2) 55 Fiberglass, 0.70" spacing, 20° angle

