113T

SINGLE LINER MED TACK MEDIA BLAST STENCIL -IBM®

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

High quality, durable, stencil coated with an advanced medium tack, rubber-based, pressure-sensitive adhesive protected by a clear polyester liner. Half inch on center hole pattern designed for IBM® sprockets. Tractor-feed holes are punched through liner and rubber.

PRODUCT APPLICATIONS

Protection of polished granite or marble, primed/painted wood, and HDU foam board during sandblasting, etching and carving processes.

STANDARD SIZES

15" x 10yd 25" x 10yd 30" x 10yd

STORAGE & SHELF LIFE

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F and 40% to 50% relative humidity are recommended. Shelf life is 12 months from date of manufacture.

intertape polymer group

100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Adhesive Medium Tack / Rubber

Total Thickness (mil) 42 (1.07mm)

PSTC-133

Tensile Strength (lbs/in) 4.5 (19.71 N/25mm)

PSTC-131

180° Adhesion to Steel (oz/in) 45 (12.32 N/25mm)

PSTC-101

Elongation (% at break) 300

PSTC-131

Punch Track

Liner Color Translucent



ANCHOR

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/23

