95gsm

POLYETHYLENE LUMBER WRAP

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

A high strength, lightweight coated fabric consisting of a reinforcing polyethylene scrim coated with polyethylene on both sides. This product is designed for effective packaging of lumber while in storage and transit

FABRIC SPECIFICATIONS

Color: White/Black
Print: up to four colours
Weight: 95 g/m² (2.80 oz/yd²)*

ROLL SPECIFICATIONS

Cores: 3 inch I.D., 4 inch I.D. or 5 inch I.D.

available

Width: Up to 136 inches (-0, +0.5") as

ordered

Length: Up to 1800 yards/roll

These values are typical data and are not intended as limiting specifications.

* Subject to change without prior notification

PERFORMANCE PROPERTIES

The following data are typical values based on ASTM standard tests. These data should not be considered specification.

Grab Tensile (N) Warp 75 lb (333)/ Weft 70 lb (310)

ASTM D5034

Tongue Tear (N) Warp 30 lb (133)/ Weft 30 lb (133)

ASTM D2261

Trapezoidal Tear (N) Warp 25 lb (111)/ Weft 20 lb (88)

ASTM D4533

Mullen Burst 120 psi (826 kPa)

ASTM D3786

Pliability -40° C or -40° F

Outdoor >80% strength retained after 6 **Weathering** months outdoor exposure



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273 Technical Service (Canada): 800.565.4533 Technical Service (US): 800.565.1450 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/14

