Indoor Carpet Tape SPECIALTY DOUBLE-COATED

DESCRIPTION

Thin, flexible vinyl (PVC) film coated on both sides with an aggressive pressuresensitive natural rubber adhesive. Excellent adhesion properties and good initial tack allowing immediate, permanent bond to a variety of surfaces (including irregular and porous surfaces). Features an easy release treated/moisture resistant flatback liner (white). Product is not repulpable.

PRODUCT APPLICATIONS

Carpet tape (hold-down and position), mounting novelties and promotional items, sign positioning, splicing, and any application that requires the joining of two surfaces.

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Vinyl (PVC) Film
Adhesive	Natural Rubber/Resin
Tensile Strength (Ibs/in of width)	15 (66 N/25mm)
Elongation (% at break)	30
Adhesion to Steel (oz/in of width)	55 (15 N/25mm)
Total Thickness (mils) With liner Without liner	9.5 (0.24 mm) 5.9 (0.15 mm)
Quick Stick to Steel (oz/in of width) PSTC-5	28 (7.7 N/25mm)
Color	Beige



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273 Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 5/18

