

# V. HIMARK CACTUS DOUBLE-COATED TAPES 2023 PRODUCT OFFERING

Effective 051623

- Jumbo, log and standard slit good formats available but may require product set up.
- Product can be converted into most custom-made sizes based on opportunity.
- External factors like shipment delays from Taiwan may cause items to be temporarily out of stock.

## CACTUS® PRODUCT OFFERING - DOUBLE-COATED PE FOAM TAPES

Model Name	Thickness	Adhesive System	Tape Color	Foam Density	Liner Material		Features & Applications	Jumbo Size (Metric)
					Type	Color		
<b>Premium Double Sided PE Foam Tapes - Higher Density Foam and High Adhesive for Long Term Bonding</b>								
B4180	1/32"	Solvent Acrylic	Black	8 PCF	PE film	Green	Side molding, Trim profile of automotive	1230mm x 300m
G4208	1/32"	Solvent Acrylic	Black	6 PCF	PE film	Lt. Blue	Quick stick & easy remove liner. UL certified	1230mm x 300m
<b>Double Sided PE Foam Tapes - Acrylic Adhesive for Window Glazing (AAMA 810.1-16, Type 1 Verified)</b>								
G488W	1/32"	Solvent Acrylic	White	4 PCF	PE film	Lt. Blue	Quick stick, high adhesion & easy remove liner	1230mm x 400m
G485W	1/16"	Solvent Acrylic	White	4 PCF	PE film	Lt. Blue	Quick stick, high adhesion & easy remove liner	1230mm x 306m
G488B	1/32"	Solvent Acrylic	Black	4 PCF	PE film	Lt. Blue	Quick stick, high adhesion & easy remove liner	1230mm x 400m
G485B	1/16"	Solvent Acrylic	Black	4 PCF	PE film	Lt. Blue	Quick stick, high adhesion & easy remove liner	1230mm x 306m
G483B	1/8"	Solvent Acrylic	Black	2.5 PCF	PE film	Lt. Blue	Quick stick, high adhesion & easy remove liner	1230mm x 140m
<b>Double Sided PE Foam Tapes - Acrylic Adhesive for Outdoor Applications</b>								
N2208	1/32"	Solvent Acrylic	White	6 PCF	Glassine paper	White	Multi purpose acrylic adhesive	1230mm x 400m
N2215	1/16"	Solvent Acrylic	White	4 PCF	Glassine paper	White	Multi purpose acrylic adhesive	1230mm x 300m
N2230	1/8"	Solvent Acrylic	White	3 PCF	Glassine paper	White	Multi purpose acrylic adhesive	1230mm x 140m
<b>Double Sided PE Foam Tapes - Rubber Adhesive for General Purpose Bonding</b>								
R2208	1/32"	Solvent Rubber	White	6 PCF	Glassine paper	White	For various substrate bonding purpose	1230mm x 400m
R2215	1/16"	Solvent Rubber	White	4 PCF	Glassine paper	White	For various substrate bonding purpose	1230mm x 300m

## CACTUS® PRODUCT OFFERING - DOUBLE-COATED FILM TAPES

Model Name	Thickness	Adhesive System	Tape Color	Backing	Liner Material		Features & Applications	Jumbo Size (Metric)
					Type	Color		
<b>Double Sided Film Tape (Solvent Acrylic Adhesive) - Transparent &amp; Enhanced Film Carrier</b>								
A2980	2.0	Solvent Acrylic	Clear	1/2 mil PET	Polycoated kraft paper	White	Ultra-thin D/S tape with high adhesion	1230mm x 1000m
K2970	3.0	Solvent Acrylic	Clear	1/2 mil PET	Glassine paper	White	Foam lamination, high/low adhesion	1370mm x 1000m
P2970	3.5	Solvent Acrylic	Clear	1/2 mil PET	Polycoated kraft paper	White	High tack adhesive, nameplates, OEM approved for Mylar / PC	1230mm x 1000m
S296R	3.5	Solvent Acrylic (clear)	Red	1/2 mil red hand-tearable PET	PE Coated kraft paper	White	High tack, high shear and high temperature resistance. Red color for visible splices. Good for zero-speed and flying splices	1230mm x 800m

Page 1 of 2

# V. HIMARK CACTUS DOUBLE-COATED TAPES 2023 PRODUCT OFFERING

Effective 051623

## CACTUS® PRODUCT OFFERING - DOUBLE-COATED FILM TAPES

Model Name	Thickness	Adhesive System	Tape Color	Backing	Liner Material		Features & Applications	Jumbo Size (Metric)
					Type	Color		
<b>Double Sided Film Tape (Solvent Acrylic Adhesive) - Transparent &amp; Enhanced Film Carrier (cont.)</b>								
P2960	6.3	Solvent Acrylic	Clear	1 mil PET	Polycoated kraft paper	White	LSE & heavy coating weight	1370mm x 600m
Y4950	6.3	Solvent Acrylic	Clear	1 mil PET	MOPP film	Pink	Economic model of Y4960	1230mm x 610m
HB296	7.8	Solvent Acrylic	Black	1/2 mil clear PET	Glassine paper	White	Light shielding for bezels / monitor frames	1050mm x 800m
Y4960	8.0	Solvent Acrylic	Clear	1/2 mil PET	MOPP film	Pink	High temperature resistance UL 969 certified	1230mm x 600m
Y251D	8.0	Solvent Acrylic	clear	2 mil UPVC	Glassine paper	Mustard	Clear carrier of Y2560	1230mm x 700m
Y2560	8.5	Solvent Acrylic	White	2 mil UPVC	Glassine paper	Mustard	High shear strength & high adhesion	1230mm x 700m
<b>Double Sided Film Tapes (Differential Adhesive)</b>								
AR29C	3.5	Solvent Acrylic & Rubber	Clear	1/2 mil PET		White	Open side: Acrylic adhesive Closed side: Rubber adhesive	1370mm x 916m
Y291M	3.5	Solvent Acrylic		1 mil PET		White	Open side: Permanent adhesive Closed side: Removable adhesive (clean removal and no residue)	1230mm x 690m

## CACTUS® PRODUCT OFFERING - DOUBLE-COATED TISSUE & PAPER TAPES

Model Name	Thickness	Adhesive System	Tape Color	Backing	Liner Material		Features & Applications	Jumbo Size (Metric)
					Type	Color		
<b>Double Sided Tissue Tape - Pliable carrier which fits the bonding surface contour &amp; is hand-tearable</b>								
H248B	5.0	Solvent Acrylic	White	Tissue	Polycoated kraft paper	White	Aggressive foam lamination	1230mm x 800m
<b>Double Sided Black Tissue Tape - Pliable carrier which fits the bonding surface contour &amp; is hand-tearable</b>								
P248E	4.3	Solvent Black Acrylic	Black	Black Tissue	Bleached kraft paper	White	For porous foam lamination. Fasten mirror tiles, plates, machine toolings, name-plates, emblems, and label. Good lightproof for shielding light electron.	1041.4mm x 825m
<b>Double-Coated Paper Tapes</b>								
M2480	7.4	Thermosetting Rubber PSA	White	Flatback paper	Glassine	White	Temporary bonding applications (carpet, textile manufacturing)	1230mm x 500m

## CACTUS® PRODUCT OFFERING - TRANSFER TAPES

Model Name	Thickness	Adhesive System	Tape Color	Backing	Liner Material		Features & Applications	Jumbo Size (Metric)
					Type	Color		
<b>Transfer / Unsupported Tape - Adhesive layer directly coated on liner. Thin but aggressive coating weight.</b>								
Y2070	4	Solvent Acrylic	Clear	Unsupported	Glassine paper	Mustard	Excellent for laminating to metal, plastics and LSE and porous surfaces.	1250mm x 55m
<b>Flame Retardant Tapes Transfer / Unsupported Tape - Adhesive layer directly coated on liner. Thin but aggressive coating weight.</b>								
W2040	2	Solvent Acrylic	Clear	Unsupported	Polycoated kraft paper	White	UL-94V0 certified Flame Retardant	1244.6mm x 165m

Page 2 of 2