RU88X-6, 350

INTERTAPE POLYMER GROUP

TECHNICAL DATA SHEET

DESCRIPTION

RU88X-6, 350 is a heavyweight fabric for applications requiring UV stability, such as membrane structure end covers and agriculture harns

FABRIC SPECIFICATIONS

Weave: Woven clear HDPE scrim

Coating: LDPE, 2.75 mil average each side

(65 g/m²/side)

Color: White, clear, green, blue, beige Weight: 10.5 oz/yd² (356g/m²) +/- 5 %

ROLL SPECIFICATIONS

Cores: 4 inch I.D. or 5 inch I.D. available Width: Up to 144 inches (-0, +0.5) as

ordered

Length: Minimum 250 yds/roll; up to 1000

vds/roll

These values are typical data and are not intended as limiting specifications.

PERFORMANCE PROPERTIES

The following data are typical values based on ASTM standard tests. These data should not be considered specification.

Thickness 20 mil (0.51 mm)

ASTM D1777

Grab Tensile Warp 400 lb 1776 N / Weft 400 lb 1776 N

ASTM D5034

Strip Tensile (N/5cm) Warp 250 lb/in (2220) / Weft 250 lb/in (2220)

ASTM D5035

Tongue Tear Warp 125 lb 555 N / Weft 125 lb 555 N

ASTM D2261

Trapezoidal Tear Warp 125 lb 555 N / Weft 120 lb 532 N

ASTM D4533

Mullen Burst 655 psi / 4512 kPa

ASTM D3786

Accelerated UV >90 % strength retention after 2000 hrs **Weathering¹** exposure @ 0.77 W/m²/nm, or 1200 hrs

ASTM G154 exposure @ 1.35 W/m²/nm

-60°C

Low Temperature Bend

ASTM D2136

¹ Q.U.V [A-340 Lamps]; 8 hrs UV @ 60°C; 4hrs condensation @ 50°C



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.565.2000 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/23