

S296R

RED DOUBLE-COATED PET WITH ACRYLIC ADHESIVE

INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

DESCRIPTION

Acrylic solvent-based adhesive tape that features a high grab tack and high adhesion adhesive system, providing quick bonding results to a wide range of materials. Hand tearable red film carrier provides dimension stability and high visibility, ideal for splicing. Good resistance to solvent, heat, and chemicals.

PRODUCT APPLICATION

High tack bonding of variety of substrates. High temperature applications. Splicing and general purpose bonding.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	0.5 mil Red PET film
Adhesive	Solvent Acrylic
Peel Adhesion (oz/in of width) PSTC-101	63.5 (1.8 kg/25mm)
Total Thickness w/o Liner (mils) PSTC-133	3.5 (0.09mm)
Shear Adhesion to Steel (hours) 1" x 1" x 2 kg 4.4 lbs PSTC-7	>24
Operating Ranges (Short Term) (Long Term)	428°F (220°C) 320°F (160°C)
Tape Color	Red
Liner	White PCK



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 10/23

