

N2230

DOUBLE-COATED PE FOAM WITH ACRYLIC

DESCRIPTION

Cactus® Double-Coated Foam Tape N2230 is an acrylic solvent-based adhesive tape that offers high shear strength and tack for secure bonding applications. Made with an easy removable liner and is reinforced with white 3 PCF cross-linked polyethylene foam tape for excellent adhesion to irregular and contour surfaces.

PRODUCT APPLICATION

Long term, indoor and outdoor mounting and joining. Permanent bonding and repair. Ideal for nameplates, signs, plastic hooks, metal and plastic houseware accessories.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 05/25

IPG®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	PE Foam
Adhesive	Solvent Acrylic
Peel Adhesion (oz/in of width) PSTC-3	105.8 (3.0 kg/25mm)
Total Thickness w/o Liner	1/8" (3mm)
Shear Adhesion to Steel 1" x 1" x 2 kg 4.4 lbs PSTC-7	>24 hours
Service Temperature	-4°F to 176°F (-20°C to 80°C)
Tape Color	White
Liner	White Glassine Paper

