

# Flagging Ribbon

## FLUORESCENT COLORS

IPG®

## TECHNICAL DATA SHEET

### DESCRIPTION

Flexible PVC (vinyl) monomeric film. 'All weather', UV, water and tear resistant. Fluorescent colors for high visibility. Contains no lead or toxic chemicals.

### PRODUCT APPLICATION

For high visibility for directional/safety. Surveying: mark and identify boundaries and property lines.

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	PVC
<b>Tensile Strength</b> (lbs/in)	11 (48 N/25mm)
<b>Elongation</b> (% at break)	280
<b>Total Thickness</b> (mil)	4.0 (0.102mm)
<b>Night Visibility</b> (w/ beam of light)	50 yards (45.7m)
<b>Colors</b>	Pink Glow, Orange Glow, Lime Green Glow



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/25

