

# AC50

## SPRAY ADHESIVE

### DESCRIPTION

Compliant with the National VOC Regulations for consumer products. 50 State compliant VOC content level 39.8% by weight. Does not contain CFCs.

### PRODUCT APPLICATION

This "web spray" aerosol adhesive has an adjustable nozzle. It's ideal for temporary or permanent bonding to uneven or porous surfaces. Works extremely well on paper, cardboard, wood, leather, carpet backings, fabrics, most plastics, glass, metal and other substrates.

Works best at room temperature (+70°F / 21°C). Hold can 6" to 8" from surface to be covered. Apply an even coating. Dries Clear in 15 minutes.

### STORAGE RECOMMENDATION

Do not expose to heat or store at temperatures above +120°F (+49°C).



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 10/25

IPG®

## TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

|                               |                         |
|-------------------------------|-------------------------|
| <b>Temperature Resistance</b> | 30                      |
| Minutes @ 160°F               |                         |
| <b>Max Temperature</b>        | +160°F (+71°C)          |
| <b>Percent Solids</b>         | 18 - 20                 |
| <b>Net Weight</b>             | 12 oz (348 g)           |
| ASTM D-3652                   |                         |
| <b>Color</b>                  | Light gray, dries clear |

