

# 594

## PREMIUM DOUBLE-COATED FLATBACK PAPER TAPE

### DESCRIPTION

A bleached flatback paper product coated with a high shear resistant pressure-sensitive natural rubber/resin adhesive on both sides that bond equally as well to almost any surface.

White easy release silicone kraft paper liner allows for either machine or hand application

### PRODUCT APPLICATION

Golf grip replacement and repair, photograph mounting, carpet installation, textile manufacturing ("twister room"), steel-rule die (make-ready), and any application that requires two adhesive surfaces for joining.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/25

IPG®

## TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Flatback Paper
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz. /in.) PSTC-101	52 (14.2 N/25mm)
<b>Thickness w/o Liner</b> (mils) PSTC-133	7 (0.178 mm)
<b>Total Thickness</b> (mils) PSTC-133	11 (0.279 mm)
<b>Temperature Resistance</b> (Max.) PSTC-133	200°F (93°C)
<b>Liner Type</b>	White SCK
<b>Tape Color</b>	Beige

