






































PERFORMANCE SERIES

Featuring Tapes You Can Rely On

| | FEATURE | MAX TEMP. FOR CLEAN REMOVAL | STRENGTH | CONFORMABILITY | MARKET |
|---|---|---|--|--|---|
| PG48 PREMIUM PERFORMANCE  | Easy & Smooth Unwind |  325°F |  Best |  Extreme |  |
| PG21 PREMIUM GRADE  | Improved Temperature Range |  325°F |  Best |  |  |
| OM PREMIUM GRADE  | High Temperature Range & Smooth Backing |  250°F |  Best |  |  |
| AM MEDIUM GRADE  | Improved Conformability |  225°F |  Better |  |  |
| MM INDUSTRIAL GRADE  | Easy & Smooth Unwind |  300°F |  Good |  |  |
| SG MEDIUM GRADE  | High Tack |  180°F |  Good |  |  |
| PM PRODUCTION MASKING  | Value Tape |  180°F |  Good |  Limited |  |



EASY & SMOOTH UNWIND

PG48

- Easy & smooth unwind
- Superior adhesion to a variety of surfaces
- Resists paint-bleed through
- High temperature resistances with 3-day UV properties



HIGH TEMPERATURE

PG21

- Fine structured crepe backing sets the standard for sharp paint lines
- Resists paint-bleed through
- Specifically designed adhesive formula to ensure superior adhesion to a variety of surfaces
- High temperature resistances with 3-day UV properties



UV RESISTANT

OM

- Exceptional conformability
- Excellent adhesion to backing to provide a secure bond and to prevent lifting and overspray
- Removes cleanly and provides a clean crisp paint line
- 3-day UV resistance



HIGH CONFORMABILITY

AM

- Excellent conformability to a variety of surfaces
- Enhanced vibrant aqua backing for high visibility of masked surfaces
- Resists paint flaking and wet sanding



EASY & SMOOTH UNWIND

MM

- High temperature adhesive
- Specially formulated to provide a secure bond and to prevent lifting and overspray
- Easy and consistent unwinds to enhance the application process



HIGH TACK

SG

- Smooth unwinds for easy of application
- Great holding power with clean removal from a variety of surfaces



VALUE

PM

- All-Purpose product for non-critical applications