



RSA 2625-TB

RANDOM SEMI-AUTOMATIC CASE SEALER

Interpack's RSA Series Case Sealers are heavy duty operator fed machines that automatically adjust for each size case processed. This new case sealer was designed to offer faster processing speeds with improved pneumatics which allows for faster bridge rise and smoother descent onto the top of the case.

This premium drive style captures the case between four moving belts located above and below the case. Maximum stability is achieved by applying force to the strongest areas of the case. Top and bottom belt drives process the widest variety of case dimensions, although certain narrow widths may be better suited on side drive belts.

Featured with the newly designed Interpack RSA case sealer is the next generation ET Xtreme™ tape head housing patented technology.



ET Xtreme™ Tape Head

MACHINE FEATURES & BENEFITS




Rapid throughput speeds with belts running at 121 ft/min




1/3 & 1/4 HP gear motors allow processing up to 85 lb cases




Best drive selection for light-weight, unstable, and void filled cases



Offset taping heads permit processing cases as low as 2" tall




Magnetic operator control box can be moved to any location



Self tensioning, self tracking belt drive simplifies belt replacement



Secondary E-Stop button



Automatically adjusts for widest variety of cases



Upper head locks to clear jams and replace tape



Pneumatic infeed gate assures proper positioning of the case

PRODUCT ATTRIBUTES

CHARACTERISTICS		RSA 2625-TB/2	RSA 2625-TB/3
Case Length Range		6" - Inf	7" to Inf
Case Width Range		6" - 26"	7" - 26"
Case Height Range	Standard	2" - 25"	2" - 25"
	Factory Adjustment	8.5" - 31.5"	8.5" - 31.5"
Case Weight		0 - 85 lbs	0 - 85 lbs
Belt Speed		121 ft/min	121 ft/min
Electric		110v., 1ph., 60hz., 6A., (1/3HP, 1/4HP)	110v., 1ph., 60hz., 6A., (1/3HP, 1/4HP)
Compressed Air Requirements		9 CFM @ 90 PSI	9 CFM @ 90 PSI
Tape Width		36 - 48 mm (1.5" - 2")	60 - 72 mm (2.5" - 3")
Conveyor Height		24" - 30"	24 7/8" - 30"
Machine Weight		730 lbs crated	730 lbs crated
Machine Dimensions (l x w x h)		56-3/8" x 41-7/8" x 63"	56-3/8" x 41-7/8" x 63"



Tip-up tape head simplifies roll replacement



One 1/3 HP motor & one 1/4 HP motor



Self-tensioning & tracking drive belts simplify belt replacement



Selectable minimum height



Horizontal centering guides with rollers



“Blocked” button for jams offset tape heads process 2" high cases



Foot pedal activated pass through mode



Secondary E-stop



Optional swivel & locking casters

OPTIONS & ACCESSORIES

- 3-inch wide tape heads
- Foot pedal activated pass through mode (top only application)
- Guarding package



ET Xtreme™

For more info on features and benefits for the ET Xtreme tape head. **SCAN HERE**



Scan for more info or visit itape.com/machines

