

NovaSeal[®]
by **Tuck**



NOVASEAL[®] ULTRA SA-HT

SELF-ADHERED ROOF UNDERLAYMENT

NOVASEAL[®] ULTRA SA-HT is a high temperature (250°F), self-adhered roofing underlayment designed for steep slope roof applications. NOVASEAL ULTRA SA-HT delivers exceptional long-term weather barrier performance compared to traditional asphalt felt products. NOVASEAL ULTRA SA-HT is designed for use under metal, asphalt shingles, synthetic shingles, primed cedar shakes, slate and tiles.

HT250
HI-TEMP ADHESIVE




FEATURES & BENEFITS



Durable, woven inner construction holds up to rugged tile, metal and slate installs



Non-woven surface is slip resistant




Horizontal marker for overlap




Limited lifetime warranty



Lighter weight & easier to handle



Strong & pliable material that resists tears & high temperatures



HT250 Hi-Temp Adhesive formulated for superior high temperature performance



UV protection for up to 90 days before final roof covering is applied



800-565-2000 | roofunderlayment.com



PROPERTIES / TEST METHOD

Product SKU	YIPGNSULTSA361A
Color	Brown with blue print
Top Surface	Slip resistant non-woven polypropylene
Bottom Release Liner	Silicone Split Release Liner
Permeability / ASTM E96-00	0.01 perms
Nominal Thickness / ASTM D1777	40 mil (1 mm)
Nail Sealability / ASTM D1970	Pass
Lap Sealability / ASTM D1970	Pass
Tensile Strength / ASTM D226	121 lbf/in. (21 kN/m)
Tear Strength / ASTM D4523	160 lbf/in. (28 kN/m)
Elongation / ASTM D2523	16%
Low Temperature Flex. / ASTM D1970	-22° F (-30°C) - Pass
Adhesion to Plywood / ASTM D1970	55 lbf/ft.:75°F (25 kgf/30.5 cm: 24°C)
Adhesion to Plywood / ASTM D1970	12lbf/ft.: 40°F (5.5 kgf/30.5 cm: 4.4°C)
UV Exposure / ASTM G90	3 months
Service Temperature / ASTM D1970	LT: 15°F (-9°C) to HT: 250°F (121°C)

ROLL / PALLET SPECS

Length per Roll	66.7' / 20.3 m
Width per Roll	36" / 91.4 cm
Weight per Roll	45 lbs / 21 kg
Square/Roll	2
Rolls per Pallet	30

NovaSeal® ULTRA SA-HT meets or exceeds all required building codes:

- ASTM D1970
- Florida Building Code FL5325
- Class A Fire ASTM E108
- CCRR 1105
- Texas Department of Insurance



Scan for more info or visit roofunderlayment.com

