




Shown with optional casters

USC 2024-BB

MAXIMUM PERFORMANCE. MINIMAL FOOTPRINT

The USC 2024-BB delivers heavyweight sealing performance in a compact, space-saving design. Twin 3-inch drive belts and a powerful gearmotor provide dependable traction and handling for heavier cases, while the self-tensioning, self-centering belt system ensures consistent performance with minimal maintenance. Tool-free belt changes and self-centering side guides make operation, setup, and maintenance fast and easy.

FEATURES



Self-centering side guide


- Easy setup
- Automatically maintain proper alignment
- Reduces maintenance requirements
- Ensures dependable operation



Twin 3" drive belts

- Delivers superior traction
- Handles heavier cases with consistent performance
- Self-tensions and centers to maintain proper alignment
- Tool-free change over reduces downtime


BENEFITS



Faster Throughput – Speeds carton sealing and line productivity



Reduced Labor Costs – Freeing workers for higher-value tasks



Consistent Seals – Delivers uniform, professional-looking carton seals

PRODUCT ATTRIBUTES

SPECIFICATIONS	USC 2024-BB	USC 2024-BB/3
Min Case (L x W x H) - ET 2Plus	7" x 7" x 4¾"	7" x 7" x 4¾"
Min Case (L x W x H) - ETX	7" x 7" x 5¼"	7" x 7" x 5¼"
Max Case (L x W x H)	Inf x 20" x 24"	Inf x 20" x 24"
Case Weight	0 - 65 lbs	0 - 65 lbs
Belt Speed	82 ft/min	82 ft/min
Electric	115v., 1ph., 60hz., 6A., (1/3HP)	115v., 1ph., 60hz., 6A., (1/3HP)
Tape Width	36 - 48 mm (1.5" - 2")	48 - 72 mm (2" - 3")
Conveyor Height	24" - 30"	24" - 30"
Machine Dimensions (L x W x H) <i>without infeed/exit tables</i>	33" x 26" x 67"	33" x 26" x 67"
Machine Dimensions (L x W x H) <i>with infeed/exit tables</i>	67.5" x 26" x 67"	67.5" x 26" x 67"

PRODUCT FEATURES



Threaded rod upper head lifting for easy height adjustment



Bottom belt drive processes heavier cases



Standard top squeezers compress the major flaps prior to taping for a more secure seal



Arcing self-centering guides make case size setup simple



ET 2 Plus tape heads included



- Twin 3" belts for improved traction versus the competition
- Simple tool-free belt change design
- Self-tensioning and self-centering belt drive
- Standard 1/3 HP gearmotor to process heavier cases
- Standard in-feed and exit tables extend the case processing area

OPTIONS & ACCESSORIES

- Heavy-duty casters (shown above)
- ET 2Plus 3" tape head
- ET Xtreme tape head

DID YOU KNOW?

IPG® is the only North American manufacturer of all 3 types of pressure-sensitive adhesives. Combine Interpack™ machinery and IPG long roll pressure-sensitive tape for greater value. Contact your authorized IPG distributor for details.



Scan for more info or visit itape.com/machines

