

# PG505 (Consumer)

## CONTRACTOR GRADE ORANGE MASKING TAPE

### DESCRIPTION

Crepe with pressure-sensitive natural rubber based adhesive. Recommended for most paint masking applications where excellent conformability and clean removal are desired.

### PRODUCT APPLICATION

General purpose masking tape designed for multiple uses for home, school and industry. Apply to clean, dry surfaces. Best results when removed within 48 hours. Not recommended for outdoor exposure

### GOVERNMENT COMPLIANCE

ASTM D6123 Type I  
C.I.D. A-A-883, Type I

### STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

### SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/26

IPG®

# TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Crepe Paper
<b>Adhesive</b>	Natural Rubber/Resin
<b>Adhesion to Steel</b> (oz/in of width) ASTM D-3330	33 (9.0 N/25mm)
<b>Tensile Strength</b> (lbs/in of width) ASTM D-3759	23 (101 N/25mm)
<b>Elongation</b> (% at break) ASTM D-3759	10
<b>Total Thickness</b> (mils) ASTM D-3652	5.8 (0.147mm)
<b>Quick Stick</b> (oz/in of width) PSTC-5	
To Kraft	5 (1.4 N/25mm)
To Steel	11 (2.7 N/25mm)
<b>Operating Temperature Range</b>	+50°F ~ +200°F (+10°C ~ +93°C)
<b>Color</b>	Orange

