

# SURFACE PROTECTION PAPER TAPE

ADHESIVE-BACKED PAPER  
(LOW TACK)

## DESCRIPTION

Paper protective tape with "low tack" adhesive with anti-slip properties. Ideal for temporary protection on boats, RVs, ATVs, vehicles inside manufacturing plants. Can be used to ease the application of large graphics to substrates as it lays flat to the exposed release liner and cut vinyl graphics to protect against wrinkling and edge curling. Adheres well to surfaces and removes cleanly after use. Since it is paper, it is recommended for indoor use. Not intended for use on delicate surfaces.

## PRODUCT APPLICATION

Temporary protection of boats inside manufacturing locations. Protection during indoor storage of molds, plugs and finished parts. Protection of patterned non-slip, gel-coat, paint, wood and countertop surfaces during boat or RV manufacturing and repair. Used during the application of large graphics to certain substrates (application tape). It is recommended the end-user spot-tests to see if this product works for their application.

## STORAGE & SHELF LIFE

Store in a cool dry place, suspended horizontally from the core; avoid exposure to sunlight. Shelf life is 1-year from date of manufacture. FOR INDOOR USE ONLY - has no UV protection and will stick aggressively when exposed to sunlight.

## STANDARD SIZES

16" x 100yds, 24" x 100yds



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

[www.itape.com](http://www.itape.com) | [info@itape.com](mailto:info@itape.com)

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/24

IPG®

# TECHNICAL DATA SHEET

## NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	Latex Saturated Paper
<b>Adhesive</b>	Natural Rubber
<b>Adhesion to Steel</b> (oz/in of width)	21 (7.6 N/25mm)
<b>Tensile Strength</b> (lbs/in of width)	20
<b>Elongation</b> (% at break)	4
<b>Total Thickness</b> (mils)	4.3
<b>Tack Level</b> (internal test)	Low
<b>Color</b>	Natural/White

