

PG5

MEDIUM GRADE PAPER MASKING TAPE

DESCRIPTION

A smooth crepe paper masking tape with a pressure-sensitive natural rubber adhesive. Offers an excellent balance of quick stick, panel adhesion and holding properties. Recommended for most paint masking applications where excellent cornering with clean removal is desired. Will support masking paper aprons at 160°F (70°C) for 30 minutes.

PRODUCT APPLICATION

Interior paint masking, spray painting autos, boats, etc., boat manufacturing (fiberglass), silk screening, mail rooms, marble manufacturing (man-made), golf club shaft (build-up), carpet pad / pad splicing, freezer tape, and bundling, packaging, splicing and tabbing.

GOVERNMENT COMPLIANCE

C.I.D. A-A-883B Type I, ASTM D6123/6123M Type I, Boeing BAC5317

STORAGE RECOMMENDATION

Store new stock behind current stock. Store in a clean, dry place. Temperature of 70°F (21°C) +/- 6°F, and 40% to 50% relative humidity are recommended.

SHELF LIFE

When stored under recommended conditions, converted rolls have an expected shelf life of up to one (1) year from the date of shipment. Jumbo rolls have the same expected shelf life, but it is recommended that they are converted within six (6) months of date of shipment.



100 Paramount Drive, Suite 300 | Sarasota, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 08/26

IPG®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	Fine Crepe Paper
Adhesive	Natural Rubber/ Resin
Adhesion to Steel (oz/in of width) PSTC-101	30 (8.2 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	25 (109 N/25mm)
Elongation (% at break) PSTC-131	10
Total Thickness (mils) PSTC-133	6.3 (0.16mm)
Quick Stick (oz/in of width) PSTC-5	
To Kraft	6 (1.6 N/25mm)
To Steel	15 (4.1 N/25mm)
Temperature Operating Range	+50° F ~ +200° F (+10°C ~ +93°C)
Colors	Beige, Orange

