

i build with



AC50UL DUCTape™

Designed by IPG® for the HVAC Industry

IPG's UL181B-FX Certified DUCTape™ products are versatile and scientifically-designed to meet the stringent requirements of the HVAC contractor. They work reliably in flexible air duct applications, and contain a polyethylene coated high-strength cloth, allowing them to stick and form with the ultimate durability and strength. IPG offers proven and recognized products sold at competitive price points to keep your costs down and your efficiency up. Below is IPG's specially-formulated offering:



AC50UL48B

AC50UL48M

AC50UL48S

View Video



TAPES & FILMS • PACKAGING PRODUCTS & SYSTEMS
BUILDING MATERIALS • ENGINEERED COATED PRODUCTS



AC50UL SPECIFICATIONS

| Backing | Adhesive | Adhesion to Steel PSTC-101 | Tensile Strength PSTC-131 | Elongation PSTC-131 | Total Thickness PSTC-133 | Temperature Range |
|--------------------|-------------------------|----------------------------------|------------------------------------|------------------------|-----------------------------|------------------------------|
| PE Coated Cloth | Natural Rubber/Resin | 75 oz/in of width (28 N/25mm) | 38 lbs/in of width (166 N/25mm) | 21% at break | 14 mils (0.356mm) | 32°F ~ 200°F (0°C ~ 82°C) |



AC50UL DUCTape™

APPLICATIONS:

- A superior closure system for flexible air ducts and connectors
- Perfect for challenging surfaces, bonding, protecting, bundling, and repair applications

FEATURES & BENEFITS:

- Meets code requirements, UL181B-FX listed
- UL723 rated, meets HUD and BOCA codes
- High strength PE coated cloth backing
- Conformable to wrap ducts for an effective seal
- Excellent bond to sheet metal and other surfaces
- High strength to withstand vertical pull from the weight of the duct system
- Resistant to moisture and mold growth, tough and durable
- Hand tearable allows for easy installation
- Rated for Class 1 duct work



OUR OFFERING

| Item # | Resource # | Description | Color | Size | Unit UPC | Carton UPC |
|-----------|------------|---------------------|----------|----------------------------------|-------------|----------------|
| AC50UL48S | 99521 | 14 mil UL AC50 - 2" | Silver | 1.88in x 60yds (48mm x 54.8m) | 77900995219 | 50077922995214 |
| AC50UL48B | 99522 | 14 mil UL AC50 - 2" | Black | 1.88in x 60yds (48mm x 54.8m) | 77922995226 | 50077922995221 |
| AC50UL48M | 99540 | 14 mil UL AC50 - 2" | Metallic | 1.88in x 60yds (48mm x 54.8m) | 7792299540 | 50077922995405 |
| AC50UL72S | 99523 | 14 mil UL AC50 - 3" | Silver | 2.83in x 60yds (72mm x 54.8m) | 77922995233 | 50077922995238 |
| AC50UL72B | 99524 | 14 mil UL AC50 - 3" | Black | 2.83in x 60yds (72mm x 54.8m) | 77922995240 | 50077922995245 |
| AC50UL72M | 99541 | 14 mil UL AC50 - 3" | Metallic | 2.83in x 60yds (72mm x 54.8m) | 7792299541 | 50077922995412 |

i build with



800-565-2000
www.itape.com | info@itape.com

©2017 Intertape Polymer Group • AC50UL SS • RV051115