

i build with



AC50UL DUCTape™

Designed by IPG® for the HVAC Industry

Intertape Polymer Group®'s UL181B-FX Certified DUCTape™ products are versatile and scientifically-designed to meet the stringent requirements of the HVAC contractor. They work reliably in flexible air duct applications, and contain a polyethylene coated high-strength cloth, allowing them to stick and form with the ultimate durability and strength. IPG® offers proven and recognized products sold at competitive price points to keep your costs down and your efficiency up. Below is IPG®'s specially-formulated offering:



AC50UL48B

AC50UL48M

AC50UL48S

[View Video](#)



TAPES & FILMS • PACKAGING PRODUCTS & SYSTEMS
BUILDING MATERIALS • ENGINEERED COATED PRODUCTS

i build with

AC50UL SPECIFICATIONS

Backing	Adhesive	Adhesion to Steel <i>PSTC-101</i>	Tensile Strength <i>PSTC-131</i>	Elongation <i>PSTC-131</i>	Total Thickness <i>PSTC-133</i>	Temperature Range
PE Coated Cloth	Natural Rubber/Resin	75 oz/in of width (28 N/25mm)	38 lbs/in of width (166 N/25mm)	21% at break	14 mils (0.356mm)	32°F ~ 200°F (0°C ~ 82°C)



AC50UL DUCTape™

APPLICATIONS:

- A superior closure system for flexible air ducts and connectors
- Perfect for challenging surfaces, bonding, protecting, bundling, and repair applications

FEATURES & BENEFITS:

- Meets code requirements, UL181B-FX listed
- UL723 rated, meets HUD and BOCA codes
- High strength PE coated cloth backing
- Conformable to wrap ducts for an effective seal
- Excellent bond to sheet metal and other surfaces
- High strength to withstand vertical pull from the weight of the duct system
- Resistant to moisture and mold growth, tough and durable
- Hand tearable allows for easy installation
- Rated for Class 1 duct work



OUR OFFERING

Item #	Resource #	Description	Color	Size	Unit UPC	Carton UPC
AC50UL48S	99521	14 mil UL AC50 - 2"	Silver	1.88in x 60yds (48mm x 54.8m)	77900995219	50077922995214
AC50UL48B	99522	14 mil UL AC50 - 2"	Black	1.88in x 60yds (48mm x 54.8m)	77922995226	50077922995221
AC50UL48M	99540	14 mil UL AC50 - 2"	Metallic	1.88in x 60yds (48mm x 54.8m)	7792299540	50077922995405
AC50UL72S	99523	14 mil UL AC50 - 3"	Silver	2.83in x 60yds (72mm x 54.8m)	77922995233	50077922995238
AC50UL72B	99524	14 mil UL AC50 - 3"	Black	2.83in x 60yds (72mm x 54.8m)	77922995240	50077922995245
AC50UL72M	99541	14 mil UL AC50 - 3"	Metallic	2.83in x 60yds (72mm x 54.8m)	7792299541	50077922995412

i build with



800-IPG-8273 / 800-474-8273

www.itape.com | E-mail: info@itape.com

©2012 Intertape Polymer Group® • AC50UL SS • RV10102012 • Printed in the U.S.A.

